

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: 11017307 A

(43) Date of publication of application: 22 . 01 . 99

(51) Int. Cl. H05K 1/18  
H01L 23/12

(21) Application number: 09169772

(71) Applicant: NEC CORP

(22) Date of filing: 26 . 06 . 97

(72) Inventor: KUSAMA TAKASHI

(54) SEMICONDUCTOR DEVICE PACKAGING  
STRUCTURE

the semiconductor device can be easily removed.

COPYRIGHT: (C)1999,JPO

(57) Abstract:

PROBLEM TO BE SOLVED: To provide a semiconductor device packaging structure which increases reliability in connection between connection terminal hidden in a package bottom surface and a printed board, and facilitates the packaging and removal of a semiconductor device.

SOLUTION: A semiconductor device 1 has guide pins 8 and conductive bumps 7. A printed board 11 has guide holes 13 for guiding the guide pins 8 and concave connection pads 14 to be in contact with the conductive bumps 7. When the semiconductor device 1 is packaged on the printed board 11, electrical connection is made by brazing the guide pins 8 to the guide holes 13, thus connecting the conductive bumps 7 to the connection pads 14. Accordingly, since it is unnecessary to braze a number of connection terminals, the packaging is simple. Further, short circuits due to the melting of the brazing material between adjacent connection pads is prevented. Further, as the semiconductor device 1 can be removed only by removing the braze of the guide pins 8,

